

# United States Patent and Trademark Office

UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.	
09/695,152	10/24/2000	Kunihiko Noguchi	450100-02779	3303	
20999	7590 11/28/2003		EXAMI	NER	
FROMMER LAWRENCE & HAUG			NGUYEN, FRANCIS N		
745 FIFTH AVENUE- 10TH FL. NEW YORK, NY 10151			ART UNIT	PAPER NUMBER	
,			2674	10	
			DATE MAILED: 11/28/2003	DATE MAILED: 11/28/2003	

Please find below and/or attached an Office communication concerning this application or proceeding.

<u> </u>	Application No.	Applicant(s)				
		7				
Office Anti-us Communication	09/695,152	NOGUCHI, KUNIHIKO				
Office Action Summary	Examiner	Art Unit -				
	FRANCIS NGUYEN					
The MAILING DATE of this communication apperiod for Reply	pears on the cover sh	eet with the correspondence address				
A SHORTENED STATUTORY PERIOD FOR REPL THE MAILING DATE OF THIS COMMUNICATION.  - Extensions of time may be available under the provisions of 37 CFR 1. after SIX (6) MONTHS from the mailing date of this communication.  - If the period for reply specified above is less than thirty (30) days, a rep - If NO period for reply is specified above, the maximum statutory period - Failure to reply within the set or extended period for reply will, by statut - Any reply received by the Office later than three months after the mailin earned patent term adjustment. See 37 CFR 1.704(b).  Status	136(a). In no event, however, ly within the statutory minimur will apply and will expire SIX (e, cause the application to bec.	may a reply be timely filed  n of thirty (30) days will be considered timely. 6) MONTHS from the mailing date of this communication. ome ABANDONED (35 U.S.C. § 133).				
1)⊠ Responsive to communication(s) filed on 11 Å	March 2003.					
2a)⊠ This action is <b>FINAL</b> . 2b)☐ This	action is non-final.					
3) Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under <i>Ex parte Quayle</i> , 1935 C.D. 11, 453 O.G. 213.						
Disposition of Claims						
4) Claim(s) 1-11 is/are pending in the application.  4a) Of the above claim(s) is/are withdrawn from consideration.  5) Claim(s) is/are allowed.  6) Claim(s) 1-11 is/are rejected.  7) Claim(s) is/are objected to.  8) Claim(s) are subject to restriction and/or election requirement.						
Application Papers	or creation requiremen					
•						
9) The specification is objected to by the Examiner.  10) The drawing(s) filed on 11 March 2003 is/are: a) accepted or b) objected to by the Examiner.						
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).						
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).						
11) The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.						
Priority under 35 U.S.C. §§ 119 and 120						
12) Acknowledgment is made of a claim for foreig a) All b) Some * c) None of:  1. Certified copies of the priority documen 2. Certified copies of the priority documen 3. Copies of the certified copies of the priority application from the International Burea * See the attached detailed Office action for a list 13) Acknowledgment is made of a claim for domest since a specific reference was included in the firm 37 CFR 1.78.  a) The translation of the foreign language priority Acknowledgment is made of a claim for domest reference was included in the first sentence of the service of the s	ts have been receive ts have been receive ority documents have but (PCT Rule 17.2(a)) to of the certified copie tic priority under 35 Urst sentence of the spovisional application tic priority under 35 Urst sentence of the Spovisional application	d. d in Application No been received in this National Stage s not received. S.C. § 119(e) (to a provisional application) ecification or in an Application Data Sheet. has been received. S.C. §§ 120 and/or 121 since a specific				
Attachment(s)						
<ol> <li>Notice of References Cited (PTO-892)</li> <li>Notice of Draftsperson's Patent Drawing Review (PTO-948)</li> <li>Information Disclosure Statement(s) (PTO-1449) Paper No(s)</li> </ol>	5) 🔲 Not	rview Summary (PTO-413) Paper No(s) ce of Informal Patent Application (PTO-152) er:				

Art Unit: 2674

#### **DETAILED ACTION**

## Response to Amendment

1. The amendment filed on 3/11/2003 is entered. The proposed drawing correction filed on 3/11/2003 is approved by the examiner.

### Claim Rejections - 35 USC § 103

- 2. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:
  - (a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.

Claims 1-8, 10-11 are rejected under 35 U.S.C. 103(a) as being unpatentable over Miichi et al. (US Patent 5,880,745) in view of Urade et al. (US Patent 6,272,644).

As to claim 1, Miichi discloses a projection display apparatus ( liquid crystal projection apparatus, see Abstract ) connected to a control device as a host ( personal computer 15 as shown in figure 5) through a serial interface ( link 16 as shown in figure 5, column, lines ), in which data is transmitted/received bidirectionally to display a picture on a display screen ( screen 14 as shown in figure 5, column 7, lines 57-58), said apparatus comprising:

display means ( liquid crystal display panel, column 7, line 14) for receiving display data from said control device and projecting a picture (OHP 13, column 6, lines 60-62) represented by said display data onto said display (screen 14 as shown in figure 1);

Art Unit: 2674

display control means for controlling a picture projected by said display means based on display control signal input ( LCD controller 43 as shown in figure 5, column 8, lines 48-49). However, Miichi fails to expressly teach input/output means connected to the control device adapted for generating display control signals controlling said display means, said input/output means being further connectable to at least one external peripheral equipment to input/output data pertaining to the supplementary information appended to input data.

Urade et al. teaches input/output means connected to the control device adapted for generating display control signals controlling said display means (USB hub 31 linked to display 30 via microcontroller 38 as shown in figure 7). Urade et al. teaches USB hub connected to a host computer and a plural of peripheral devices (column 4, lines 57-61, also figure 7), bidirectional data transfer between hub controller and microcontroller (column 5, lines 29-32). It would have been obvious to a person of ordinary skill in the art at the time of the invention to utilize the apparatus of Miichi, then couple the USB hub 31 as taught by Urade et al. to personal computer 15 in apparatus of Miichi for bi-directional interface link and connect the USB hub to the OHP projector for providing connection to extra peripheral devices to obtain the combined apparatus Miichi modified by Urade et al. because it would result in expanding connectivity to a plurality of devices, bi-directional data communication, and also flexible power control of USB devices as taught by Urade et al. (column 4, lines 36-47).

As to claim 2, see the same citation for claim 1. The projection display apparatus of claim 1 wherein said input/output means is a hub conforming to the USB (Universal Serial Bus)

Art Unit: 2674

standard (apparatus Miichi modified by Urade et al. comprises USB Hub 31 shown in Urade et al. figure 7) and is connected to the control device having an interface conforming to the USB standard (note Urade et al. teaches USB hub 11 connected to host computer, column 4, lines 57-61 and controlling device is personal computer 15 of Miichi, also USB interface 37 is taught in figure 7 of Urade et al., and to an external peripheral equipment having an interface conforming to the USB standard (see Urade et al., column 1, lines 15-17, printer, keyboard, also see Urade et al. column 1, lines 30-34, devices include USB interface and a USB logical device).

As to claim 3, the projection display apparatus according to claim 1, wherein an operating input device ( Urade et al. teaches keyboard, column 1, lines 14-15) for generating an operating input signal as an external peripheral equipment is connected to said input/output means ( Urade et al. already teaches a keyboard connected to USB hub, see column 1, lines 30-34, also USB Hub 31 provides a plurality of USB device ports 32-35 shown in figure 7 ) and wherein said display control means controls a picture projected by said display means ( LCD controller shown in figure 5) in accordance with a pointer control signal ( Miichi teaches mouse 18 for pointer control signals ( as shown in figure 1) from the control device ( figure 1 of Miichi teaches personal computer 15 as shown in figure 5) based on the operating input signal generated in said operating device ( note Urade et al. aforementioned teaching of USB keyboard).

Art Unit: 2674

As to claim 4, see the same citation for claim 1. The projection display system according to claim 1 wherein a second projection display apparatus is connected as an external peripheral device to said input/output means (note Urade et al. teaching devices including monitors (column 1, lines 14-15) as devices having USB interface in communication with hub repeater, column 1, lines 30-34, multiple ports for accommodating multiple USB devices in figure 3, it is obvious to a person of ordinary skill in the art to connect another projection display apparatus ) and wherein said input/output means outputs display data and the display control signals from the control device to said second projection display apparatus (note Urade et al. teaches USB hub controller and hub repeater, column 1, lines 25-34, this allows connections of a plurality of USB devices; therefore communications from personal computer 15 of Miichi to a second projection display apparatus is then inherent because of the hub function.

As to claim 5, Miichi teaches a projection display system (see Abstract) in which a control device as a host and a projection display apparatus as a target controlled by said control device are interconnected over a serial interface (personal computer 15 in figure 5 connected to OHP 13 as shown in figure 1), and in which data transmission/reception is made bidirectionally at least between said control device and said projection display apparatus to project a picture by said projection display apparatus on a display screen (screen 14 shown in figure 1), wherein

said projection display apparatus includes display means (LCD panel column 7, lines 14-15, shown in figure 5) for receiving display data from said control device and projecting a

Page 6

Application/Control Number: 09/695,152

Art Unit: 2674

picture represented by said display data onto said display screen (screen 14 shown in figure 5), and display control means for controlling a picture (LCD controller 43 as shown in figure 5) projected by said display means based on a display control signal input (input from personal computer 15 of figure 5. However Miichi fails to teach input/output means connected to the control device adapted for generating display control signals controlling said display means, said input/output means being further connectable to at least one external peripheral equipment to input/output data pertaining to supplementary information appended to input data. Urade et al. teaches input/output means connected to the control device adapted for generating display control signals controlling said display means ( USB hub 31 linked to display 30 via microcontroller 38 as shown in figure 7, also note LCD controller 43 in figure 5 controlling LCD unit 44 as shown in figure 5). Urade et al. teaches USB hub connected to a host computer and a plural of peripheral devices (column 4, lines 57-61, also figure 7)), bidirectional data transfer between hub controller and microcontroller (column 5, lines 29-32). It would have been obvious to a person of ordinary skill in the art at the time of the invention to utilize the apparatus of Miichi, then couple the USB hub 31 as taught by Urade et al. to personal computer 15 in apparatus of Miichi, link the USB hub to the OHP to obtain the combined apparatus Miichi modified by Urade et al. because it would result in expanding connectivity to a plurality of devices, for bi-directional interface link, and also flexible power control of USB devices as taught by Urade et al. (column 4, lines 36-47).

As to claim 6, see the same citation for claim 5. The projection display a system according to claim 5 wherein the input/output means of the projection display apparatus is a hub (USB hub

Art Unit: 2674

pursuant to the USB (Universal Serial Bus) and is connected to an external peripheral equipment having an interface conforming to the USB standard (Urade et al. teaches devices including printers, keyboards (column 1, lines 14-15) as devices having USB interface in communication with hub repeater, column 1, lines 30-34) and wherein the input/output means of the control device is an interface pursuant to the USB standard (apparatus Miichi modified by Urade et al. teaches microcontroller 38 connected to USB hub 31 via microcontroller interface 37, see Urade et al. figure 7).

As to claim 7, the projection display system according to claim 5 wherein there is provided an operating input device (Urade et al. teaches keyboard, column 1, lines 14-15) connected as an external peripheral device—to said input/output means of said projection apparatus to generate an operating input signal, and wherein said display control means controls a picture projected by said display means on said display screen—(OHP 13 shown in figure 1, LCD controller 43 shown in figure 5) in accordance with a pointer control signal—(Miichi teaches mouse 18 shown in figure 1)—from said control device—(personal computer 15 shown in figure 5) which is based on the operating input signal generated in said operating input device (note Urade et al. aforementioned teaching of USB keyboard).

As to claim 8, see the same citation for claim 5. The projection display system according to claim 5 wherein said projection display apparatus is a first projection display apparatus, and a second projection display apparatus is connected as an external peripheral device to said input/output means of said first projection display apparatus (note Urade et al. teaching devices including monitors (column 1, lines 14-15) as devices having USB interface in

Art Unit: 2674

communication with hub repeater, column 1, lines 30-34, multiple ports for accommodating multiple USB devices in figure 3, it is obvious to a person of ordinary skill in the art to connect another projection display apparatus ) and wherein the input/output means of said first projection display apparatus outputs display data and the display control signal from the control device to said second projection display apparatus (note Urade et al. teaches USB hub controller and hub repeater, column 1, lines 25-34, this allows connections of a plurality of USB devices; therefore communications from personal computer 15 of Miichi to a second projection display apparatus is then inherent because of the hub function.

As to claim 10, Miichi modified by Urade et al. teaches receiving means for receiving (receiver 45 shown in figure 1) a remote control signal from a remote control device (remote controller 1 shown in figure 1, column 7, lines 43-49) and providing a detection signal in response thereto (input signal to MPU 39 shown in figure 5), wherein said display control means outputs a pointer control signal to said display means to shift a pointer (cursor keys 5-8 shown in figure 2 serve to shift a pointer) included in said picture projected by said display means responsive to said detection signal from said receiving means (image signal on basis of process predetermined in the position specified by mouse 18, column 7, lines 5-8).

As to claim 11, Miichi modified by Urade et al. teaches the projection display system according to claim 5 (see same citations for claim 5), wherein said projection display apparatus further comprises receiving means for receiving (receiver 45 shown in figure 1) a remote control signal from a remote control device (remote controller 1 shown in figure 1, column 7, lines 43-

Art Unit: 2674

49) and providing a detection signal in response thereto (input signal to MPU 39 shown in figure 5), wherein said display control means outputs a pointer control signal to said display means to shift a pointer (cursor keys 5-8 shown in figure 2 serve to shift a pointer) included in said picture projected by said display means responsive to said detection signal from said receiving means (image signal on basis of process predetermined in the position specified by mouse 18, column 7, lines 5-8).

3. Claim 9 is rejected under 35 U.S.C. 103(a) as being unpatentable over Miichi in view of Urade et al. and further in view of Nguyen et al. (US Patent 5,682,181).

As to claim 9, Miichi modified by Urade et al. fails to teach control means switching the application program generating the display based on the operating input signal. Nguyen et al. teaches a control means switching the application program generating the display based on the operating input signal: method and display control system for a projection display system, see abstract, teaching main menu window 60 with different selections, switching from main menu window 60 to draw window 80 ( column 5, line 40 through column 6, line 5) based on user selection. It would have been obvious to a person of ordinary skill in the art the time of the invention to utilize the apparatus Miichi modified by Urade et al., then modify the software by Miichi to include menu selection of applications as taught by Nguyen et al., to obtain the combined apparatus Miichi modified by Urade et al and Nguyen et al., because it would provide user greater flexibility to select appropriate software application by menu selection.

Art Unit: 2674

This corresponds to the projection display system according to claim 7 wherein said control device includes operating input means adapted for being actuated to generate said operating input signal (Note Miichi teaching aforementioned mouse 18 in figure 5 as operating input means), said control means switching the application program (Nguyen et al. aforementioned teaching of main menu window/draw window) generating the display based on the operating input signal from said operating input, means or the operator input device connected to the projection display apparatus.

## Response to Arguments

4. Applicant's argument filed on 3/11/03 has been fully considered but is not persuasive. Applicant's argument as to cited art failing to teach input/output means connected to the control device is not valid because the USB hub of Urade et al. does have a root port 13 (figure 3) for linking to a host computer (column 3, lines 40-41).

Applicant's argument as to cited art failing to teach input/output means further connected to an external peripheral equipment is not valid because the USB hub of Urade et al. does have ports 1-4 (figure 3) to accommodate external peripheral devices.

Applicant's argument as to cited art failing to teach input/output means as part of the projection apparatus is not valid because the combined apparatus Miichi modified by Urade et al. has the USB hub combined with the OHP ( see above rejection). Since the USB hub has a root port ( Urade et al. figure 3), it makes sense that it is electrically linked to the host computer, but not combined with the host computer, as Applicants thought.

Application/Control Number: 09/695,152 Page 11

Art Unit: 2674

Applicant's argument as to cited art failing to teach receiving means for receiving a remote control signal is not valid because Miichi does teach a receiver 45 (shown in figure 1) for reciving a remote control signal from remote control device (remote controller 1 shown in figure 1, column 7, lines 43-49)

The pending claims, due to lack of claim breadth, remain rejected.

#### Conclusion

5. The prior art made of record is not relied upon, but pertinent to Applicant's disclosure:

US Patent Furuhata 6,345,897

US Patent Lee 6,587, 053

US Patent Endo 6,363,491

Reference Furuhata is made of record as it discloses a projection display device and remote controller.

Reference Lee is made of record as it discloses a wireless key input processing apparatus using a Universal Serial Bus.

Reference Endo is made of record as it discloses a USB apparatus and a USB hub apparatus.

6. Applicant's amendment necessitated the new ground(s) of rejection presented in this Office action. Accordingly, **THIS ACTION IS MADE FINAL**. See MPEP § 706.07(a). Applicant is reminded of the extension of time policy as set forth in 37 CFR 1.136(a).

A shortened statutory period for reply to this final action is set to expire THREE

MONTHS from the mailing date of this action. In the event a first reply is filed within TWO

Art Unit: 2674

MONTHS of the mailing date of this final action and the advisory action is not mailed until after the end of the THREE-MONTH shortened statutory period, then the shortened statutory period will expire on the date the advisory action is mailed, and any extension fee pursuant to 37 CFR 1.136(a) will be calculated from the mailing date of the advisory action. In no event, however, will the statutory period for reply expire later than SIX MONTHS from the date of this final action.

7. Any inquiry concerning this communication or earlier communications from the examiner should be directed to FRANCIS N NGUYEN whose telephone number is 703 308-8858. The examiner can normally be reached during hours 8:00 AM- 4:30 PM.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, **RICHARD A HJERPE** can be reached at 703 305-4709.

Any response to this action should be mailed to:

Commissioner of Patents and Trademarks

Washington, D.C. 20231

or faxed to:

(703) 872-9314 (for Technology Center 2600 only)

Hand-delivered responses should be brought to Crystal Park II, 2121 Crystal Drive, Arlington, VA, Sixth Floor (Receptionist).

Any inquiry of a general nature or relating to the status of this application or proceeding should be directed to the Technology Center 2600 Customer Service whose telephone number is (703) 306-0377.

Art Unit: 2674

FRANCIS N NGUYEN Examiner

Art Unit 2674

6

FN

November 20th, 2003

RICHARD MJERPE

SUPERVISORY PATER EXPERIEN

TECHNOLOGY CENTER 2000